

Modello	Tensione	Corrente	Alimentazione		Capacità Batteria Ah (C5)			Modulo
			Ampere (A)	Vac	8h	10h	12h	
N1210	12 V	10:00 AM	2	90 – 130 Vac	80	100	120	1
N1215		15 A	2		o	120	150	180
N1220		20 A	2	180 – 264 Vac	160	200	240	1
N1225		25 A	2		200	250	300	2
N2410	24 V	10:00 AM	2	90 – 130 Vac	80	100	120	1
N2415		15 A	2		o	120	150	180
N2420		20 A	3	180 – 264 Vac	160	200	240	1
N2425		25 A	3		200	250	300	2
N2430		30 A	4		240	300	360	3
N2435		35 A	4		280	350	420	4
N2440		40 A	5		320	400	480	4
N2450		50 A	6		400	500	600	4
N3610	36 V	10:00 AM	2	90 – 130 Vac	80	100	120	1
N3615		15 A	2		o	120	150	180
N3620		20 A	4	180 – 264 Vac	160	200	240	1
N3625		25 A	5		200	250	300	2
N3630		30 A	6		240	300	360	3
N3650		50 A	9		400	500	600	5
N4812	48 V	12:00 AM	3	90 – 130 Vac	80	100	120	1
N4815		15 A	4		o	120	150	180
N4820		20 A	6	180 – 264 Vac	160	200	240	2
N4825		25 A	8		200	250	300	2
N4830		30 A	8		240	300	360	4
N4835		35 A	10		280	350	420	4
N4840		40 A	10		320	400	480	5
N4850		50 A	12		400	500	600	5
N4870		70 A	14		400 Vac	560	700	840
N7210	72 V	10:00 AM	4	90 – 130 Vac	80	100	120	2
N7215		15 A	6		o	120	150	180
N7220		20 A	8	180 – 264 Vac	160	200	240	3
N7225		25 A	8		200	250	300	4
N7230		30 A	11		240	300	360	5
N7235		35 A	13		280	350	420	6

TCE Group Srl